# PJD6211

DLP PROJECTOR WITH BRILLIANTCOLOR™

120Hz, 3D READY

## Price/performance leader in portable DLP projectors.

ViewSonic's PJD6211 DLP® projector is ideal for use in the office or on the road. It delivers amazingly clear images with the digital clarity of DLP's BrilliantColor™ technology. This budget-friendly projector boasts amazingly fast 120Hz frame rate and is 3D ready for graphic renderings in the office or 3D games or movies at home. With high contrast ratio and brightness and ViewMatch™ technology to adjust colors perfectly, your presentations will be rich, vibrant regardless of the setting. This projector is a lightweight powerhouse that offers multiple inputs, including support for 720p and 1080i HDTV signals. Eco-mode extends lamp life and reduces fan noise. Enjoy easy set up with auto source detection and auto sync. When you're done, just unplug it and go. The PJD6211 DLP projector delivers excellent performance and value for small business and home entertainment applications.



#### > Advanced six segment color wheel

Optical Engine is using advanced DDR DMD chip. The picture is smoothly without cell gap to provide saturated color and sharp image.

#### > Bright in virtually any setting with 2,500 lumens

Packs 2,500 lumens in just 2.66kg. It's the bright choice for mobile presenters.

#### > BrilliantColor™ technology

DLP® projectors with BrilliantColor™ feature multi-color processing to produce nearly 50% brighter colors for a vibrant image on the screen that won't fade over time.

#### > Eco-mode extends lamp life

Extend the life of your lamp up to 5,000 hours\*\* and reduce noise output.

#### > Off-to-Go feature

The direct off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.

















# PJD6211



### DLP PROJECTOR WITH BRILLIANTCOLOR™







#### **Optional Accessories**

>Replacement lampRLC-I	050
>Wireless presentation gatewayWPG-	350
>Ceiling mountWMK-	)25
>Soft case	368
>Remote control w/Laser pointer A-00008	495

Projection Distance		4 : 3 Screen Screen Size			
		Wide		Tele	
M	feet	m	inch	m	inch
1.5	4.92	1.17	46.14	0.99	39
1.8	5.90	1.41	55.36	1.18	47
2	6.56	1.56	61.52	1.32	52
3	9.84	2.34	92.27	1.97	78
5	16.40	3.91	153.79	3.29	130
10	32.80	7.81	307.58	6.58	259







ViewSonic Corporation`s QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)		
DISPLAY	Resolution	XGA 1024×768 (Native) / UXGA 1600×1200 (compressed)		
	Lens	1.2× Manual optical zoom / Manual optical focus  Vertical digital keystone correction: ± 40 degrees  30"-300"		
	Keystone			
	Size			
	Throw Distance	1.2m-10m 1.6:1-1.9:1		
	Throw Ratio			
	Lamp	180watt (RLC-050)		
	Lamp Life	4000 / 5000 hrs 2,500 Lumens 2000:1		
	Brightness			
	Contrast Ratio			
	Aspect Ratio	4:3 & 16:9		
	Colour Depth			
	Colour Depth Colour Wheel	30 bits, 1.073 B Colour (10 +10+ 10)		
	Colour vvneel Colour Gamut	6-Seg RGBCYW / 7200rpm		
AUDIO		85 % NTSC 1931 CIE		
INPUT SIGNAL	Speaker	2W x 1		
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and		
		576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps)		
	F	HD 720p, 1080i (24fps, 25pfs and 30fps)		
COMPATIBILITY	Frequency	Fh: 31-100 KHz, Fv: 50-120 Hz		
COMPATIBILITY	PC	VGA to UXGA		
CONNECTOR	Mac	Up to 1152×864 (may require Mac Adapter)		
CONNECTOR	RGB Input	2 × 15-pin mini D-sub		
	RGB Output	1 × 15-pin mini D-sub		
	Composite Input	1 × RCA jack		
	S-Video Input	1 × 4-pin mini-DIN		
	Audio Input	$1 \times 3.5$ mm mini jack		
	Audio Output	$1 \times 3.5$ mm mini jack		
	Control	1 × RS-232 (9 Pin D-sub)		
	USB	1 x type B (Firmware upgrade)		
	Power	12 V DC Connector		
POWER	Voltage	90~240VAC(Auto Switching), 50/60Hz (universal)		
	Consumption	235W (Typical) / <1W (Stand-by mode)		
OPERATING	Normal / Eco Mode	31dB / 29dB		
LANGUAGE		English / Dutch / French / Spanish / Italian / Korean / Thai / Portuguese		
		T. Chines / S. Chinese / Japanese / Russian / German / Swedish / Turkish /		
		Finnish / Polish		
CONTROLS	Basic	POWER, Keystone/Arrow keys, Left/BLANK, MENU/EXIT, Right/Panel key		
	OSD	lock, AUTO, MODE/ENTER, SOURCE		
		Picture: Brightness, Contrast, Color Setting, Keystone, Aspect Ratio		
		Image, White Intensity, Gamma, 3D Sync, 3D Sync Invert.		
		Computer Image: Frequency, Tracking, H Position, V Position		
		Video Image: Saturation, Sharpnes, Tint		
		Setting: Manu Position, Projection, Signal Type, Lamp Hour, Lamp Hour		
		Reset, Filter Mode, Filter Hours, Filter Hours Reset, Power Saving, Auto		
		Source, ECO Mode, High Altitude, OSD Timeout		
		Advance: Blank Screen, Password Word, Screen Capture, Start up Screen		
		Text Shot: Digital Zoom, DCR, Close Captions, Brilliant Color		
OPERATING	Temperature	0°C-40°C (32°F-104°F)		
CONDITION	Humidity	10%-80% (non-condensing)		
	Altitude	0~6,000 ft (1,800 m), operational up to 10,000 ft (3048 m) at reduced		
		reliability and performance		
DIMENSIONS	Physical	280 x 114 x 218 (mm) / 11 x 4.5 x 8.58 (in)		
(W x D x H)	-			
WEIGHT	Net	2.66 kg (5.86 lb)		
		CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOM		

Headquarters:

381 Brea Canyon Road, Walnut, CA 97189, U.S.A. salesinfo@viewsonic.com Asia Pacific:

9F, No. 1 92 Lien Chien Road, Chung Ho, Taipei, R.O.C. www.viewsonic.com.tw

ViewSonic Singapore: 1 Kaki Bukit Road 1 #03-40 Enterprise One,

Singapore 415934

ViewSonic Australia: Unit 4, 44 Dickson Ave, Artarmon NSW 2064, Australia www.viewsonic.com.au

PACKAGE CONTENTS

ViewSonic Korea:

#622, 6F, Gangbyeon Hanshin Core Bldg., 350, Mapo-dong Mapo-gu, Seoul 121-703, Korea

ViewSonic India: Unit No 2, 3 &4, Ground Floor, Tribhuvan Complex, Ishwar Nagar, Mathura Road, New Delhi – 110065

ViewSonic projector, power cable, VGA cable, remote control with batteries, lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide) Rev.1.0

PSB, C-tick, CE, TUV, GOST-R, Hygienic, UKrSEPRO, CCC

ViewSonic Middie East & Africa Dubal U.A.E, PO Box 17625 me.viewsonic.com ap.viewsonic.com/za